

Alstron ALT Series Ultrasonic Cleaner provides a comprehensive range of units tailored for industrial part cleaning. Applications cover degreasing and removing contaminants from various components including marine vessels, aerospace parts, PCBs, machining parts, mechanical components (pre-coating or plating), optical parts, surgical instruments, 3D modeling, R&D, and more.

- Signature Frequency 120kHz for General Cleaning Applications
- Internal Tank - Stainless Steel SS316L, External Tank - SS304 Construction
- Adjustable Digital Timer for Ultrasonic Duration Control
- Digital Temperature Controller for Heating Control
- Sweeping Function & Adjustable Ultrasonic Power Intensity
- PLL Technology with Auto-Frequency Tracking & Adjustment
- Power Input: 415V, 3 Phase
- Water Drainage Piping & Valve in SS316
- Castor Wheel with Brakes for Easy Transportation or SS316L Base Structure for Vessels



Model	ALT-1202750-420H-3
Functional	
Frequency	120
Capacity (Litres)	420
Ultrasonic Power (Watts)	2750
Sweeping Function	Yes
Power Intensity	10 - 100% Adjustable
Timer Function	1 - 60 mins / Infinity
Immersion Heater Power (Watts)	6000
Temperature Sensor Type	PT100
Temperature Range (Celsius)	20 – 70 °C
Connected Power (Ampere)	32 (5-pin)
Input Power	AC 415V, 3 Phase, 50/60Hz
Programmable HMI (Touchscreen)	Not Applicable
Tank	
Internal Tank Dimension L x W x H (mm)	1150 x 580 x 630
Overall External Tank Dimension w/o Valve (mm)	1250 x 865 x 910 (+ 150 mm with Base Support)
Internal Tank Material	SS316L
External Tank Material	SS304
Net Weight (kg)	245
Water Inlet Valve	SS316, ½ Inch Full Ball Valve
Drainage Valve Material	SS316, 1 ½ Inch Full Ball Valve
Power Cable Length	3m with Quick Connector and 5-Pin Wall Plug
Basket	
Basket Internal Dimension L x W x H (mm)	1126 x 560 x 570
Basket Material	SS316L
Mesh Grid Size (mm²)	25 x 25
Optional	
High Density Basket Model	ABK-1202750-01
Mesh Grid Size (mm²)	5 x 5