ALT Series Ultrasonic Cleaner

Alstron ALT Series Ultrasonic Cleaner provides a comprehensive range of units tailored for industrial part cleaning.

Applications cover degreasing and removing contaminants from various components, including manufacturing, marine vessels, aerospace parts, PCBs, machining parts, mechanical components (pre-coating or plating), optical parts, surgical instruments, 3D modelling, laboratory R&D, printing and packaging industry, scuba diving, jewellers, and more.

Floor Standing 24L Ultrasonic Cleaner with SS316 Drain Valve



Signature 33 kHz Operating Frequency
For general cleaning applications.

Durable Stainless Steel Construction
Internal 316L and external 304.
Holding Basket
Strong stainless steel 316 with 1sq-in mesh.

Digital Timer
Adjustable from 1-60 minutes or infinite.
Digital Temperature Controller
Adjustable from 20-70°C.

Variable Power Control
Adjustable from 10-100%.

Sweeping & PLL Features
Modulates frequency for complete coverage and auto-adjusts for consistent performance.

ALT-33600-24H	
Technical Data – Electrical	
Frequency (kHz)	33
Input Power	AC 220 – 240 V, Single Phase, 50/60Hz
Connected Power (Ampere)	13
Ultrasonic Power (Watts)	600
Heater Power (Watts)	900
Temperature Sensor Type	PT100
Technical Data – Mechanical	
Capacity (Litres)	24
Internal Tank Dimensions L x W x H (mm)	400 x 300 x 200
External Tank Dimensions L x W x H (mm)	456 x 356 x 485
Net Weight (kg)	28
Internal Tank Material	SS316L
External Tank Material	SS304
Drainage Valve Material	SS316, 3/4 Inch Full Ball Valve
Power Cable Length	3m with Quick Connector, BS1363 UK Plug
Basket	
Basket Internal Dimensions L x W x H (mm)	370 x 270 x 130
Basket Material	SS316L
Mesh Grid Size (mm²)	25 x 25
Optional	
High Density Basket Model	ABK-33600-01
Mesh Grid Size (mm²)	5 x 5

Technical Specifications subject to tolerances due to manufacturing.

Copyright @ 2024 Alstron (Singapore) Pte Ltd. All rights reserved.