## <u>ALSTRON</u>

# **ALTC Series Ultrasonic Cleaner**

Alstron ALTC Series Ultrasonic Cleaner provides a comprehensive range of economic units tailored for industrial part cleaning.

The -3NN type is specifically designed for marine vessels, with applications that include degreasing and removing contaminants from components and equipment such as engines, transmission systems, deck fittings, heat exchangers, stern drive parts, mechanical linkages, injection nozzles, stainless steel filter candles, separator spare parts, and components of heating and cooling systems.

#### For Marine

Compatible with Vessel power supply; 440Vac, 3 Phase + E power input.


### **Signature 120 kHz Operating Frequency** For general cleaning applications.

Durable Stainless Steel Construction

Internal and external 304 Holding Basket Strong stainless steel 304 with 1sq-in mesh.

#### **Digital Timer**

Adjustable from 1-60 minutes or infinite. **Digital Temperature Controller** Adjustable from 20-70°C.





420L Ultrasonic Cleaner with Castor Wheels\*, SS304 Inlet & Drain Valve

### **Sweeping & PLL Features**

Modulates frequency for complete coverage and auto-adjusts for consistent performance.

\*Optional – Stainless Steel 304 Base Structure for secure marine vessel mounting.

| ALTC-1202750-420H-3NN                     |  |
|---|--|
| Technical Data – Electrical               |  |
| Frequency (kHz)                           | 120  |
| Input Power                               | AC 440V, 3 Phase + E, 50/60Hz                                      |
| Connected Power (Ampere)                  | 32   |
| Ultrasonic Power (Watts)                  | 2750   |
| Heater Power (Watts)                      | 6000   |
| Temperature Sensor Type                   | PT100  |
| Technical Data – Mechanical               |  |
| Capacity (Litres)                         | 420  |
| Internal Tank Dimensions L x W x H (mm)   | 1150 x 580 x 630   |
| External Tank Dimensions L x W x H (mm)   | 1250 x 865 x 910 (+ 150 mm with Base Support)                      |
| Internal Tank Material                    | SS304  |
| External Tank Material                    | SS304  |
| Net Weight (kg)                           | 135  |
| Water Inlet Valve                         | SS304, ½ Inch Full Ball Valve                                      |
| Drainage Valve Material                   | SS304, 1 ¼ Inch Full Ball Valve                                    |
| Power Cable Length                        | 3m with Quick Connector and 4-Pin Plug                             |
| Basket                                    |  |
| Basket Internal Dimensions L x W x H (mm) | 1126 x 560 x 570   |
| Basket Material                           | SS304  |
| Mesh Grid Size (mm <sup>2</sup> )         | 25 x 25  |
| Optional                                  |  |
| High Density Basket Model                 | ABK-1202750-01   |
| Mesh Grid Size (mm <sup>2</sup> )         | 5 x 5  |
|   | Technical Specifications subject to tolerances due to manufacturin |

Technical Specifications subject to tolerances due to manufacturing.

www.alstron.com.sg